

Mast type	Maximum Fork Height	Maximum Lowered Height	Fully Extended Height	Free Lift	Rated Load Capacities							
					B35X-7							
					with Load Backrest	with Load Backrest	Tilt Angle				Load Capacities	
							Single Pneu.		Single Solid		Single Pneu	Single Solid
deg	deg	FWD	BWD	FWD	BWD	LC500mm	LC500mm					
	mm	mm	mm	mm	deg	deg	deg	deg	kg	kg		
STD	2,720	2,020	3,970	152	6	9	6	9	3,500	3,500		
	3,000	2,160	4,250	152	6	9	6	9	3,500	3,500		
	3,495	2,410	4,750	152	6	9	6	9	3,500	3,500		
	3,655	2,560	4,905	152	6	9	6	9	3,500	3,500		
	3,805	2,635	5,055	152	6	9	6	9	3,500	3,500		
	4,805	3,135	6,055	152	6	5	6	9	3,125	3,425		
FF	2,720	2,020	3,970	820	6	5	6	9	3,500	3,500		
	3,000	2,160	4,250	960	6	5	6	9	3,500	3,500		
	3,495	2,410	4,745	1,210	6	5	6	9	3,500	3,500		
FFT	3,555	1,885	4,805	685	6	9	6	9	3,400	3,400		
	3,960	2,020	5,210	820	6	9	6	9	3,400	3,400		
	4,380	2,160	5,630	960	6	9	6	9	3,300	3,400		
	4,820	2,330	6,070	1,130	6	5	6	9	3,175	3,400		
	5,205	2,510	6,455	1,310	6	5	6	9	2,575	3,300		
	5,655	2,660	6,905	1,460	6	5	6	5	2,000	3,200		

Note: These load capacities are based on the standard chassis without side shifter.
 Specification values quoted in this catalog have been rounded.
 Products and specifications are subject to improvement and change without notice.
 Performance may vary due to operating conditions.
 The performance shown represents nominal values obtained under typical operating conditions.

7-Series Forklifts

Electric 2.2 to 3.5 ton capacity



EUB25X7-160205v1EN (February 2016)



Doosan Industrial Vehicle Europe nv
 Europark-Noord 36A
 9100 Sint-Niklaas
 Belgium
 Tel.: +32 3 760 09 87
 Fax: +32 3 760 09 89
 Website: www.doosan-iv.eu

AUTHORIZED DEALER

Lifting Your Dreams

