

## PA12.7V

## Air Compressors

Specifications

## General Data

General Data		Dimension
Emission Compliance Free Air Delivery (RANGE) Rated Operating Pressure (RANGE)	Stage V 7,0-5,2 m3/min. 5,5-12,1 bar	• • • • • • • • • • • • • • • • • • • •
Engine		Ka Bobcal
Make Model Number of Cylinders Full load speed Power Electrical Cooling Fuel Tank capacity	HDI D24 4.0 2550.0 RPM 54.7 kW 12 V Water 130.60 L	Values with "*" are measured on shipping support (A) 3480.0 mm (B*) 1254.0 mm (A) 2371.0 mm (C) 1545.0 mm (A*) 2371.0 mm (C*) 1249.0 mm (B) 1754.0 mm
Sound Level Data Fully compliant to outdoor noise directive 2000/14/EC (2006)	98 dB(A)	
Weights		
Weight (net) fixed/adjustable Weight (working) fixed/adjustable Weight max (ref. Dataplate) Weight on shipping support (net) Weight on shipping support (working)	1106kg / 1152 kg 1214kg / 1260 kg 1500 kg 945 kg 1053 kg	
Standard Features		
Central lifting point Fuel/water separator Flex Air system "Push after warm-up" button Bunded base with 110% fluids containment with central drains Document box Polymer Canopy Jockey Wheel LED CE and UK (13 pins) Battery isolator	Emergency stop Low Fuel Light including fuel switch Diesel particulate filter Spark Arrestor 28mm tow eye 40mm tow eye 50mm tow eye 68mm tow eye 50mm tow eye 50mm ball hitch	